

HELPHY GSM-S

Alarm system for lift-car top installation, complete with GSM module




- Autodialer with built-in speaker unit & GSM module
- Top-car installation
- Embedded batteries
- Programmable via e-stant software

Dimensions: 182 x 123 x 61 mm
Weight: 629 g

Product	Part number	Description
HELPHY GSM-S	5HG-001/S	HELPHY GSM-S: autodialer in a resistant box, complete with:
		- GSM module - backup batteries - speaker unit - power supply - mains cable - alarm pushbutton - reset pushbutton - signalling LEDs - antenna with magnetic base and cable L = 2 m

Main Features

- Telephone numbers: programmable, up to 12
- Supported voice terminals: up to 2 passive speaker units, 2 active speake units
- Digital volume adjustment
- Local programming: telephone (DTMF tones), micro SD card, computer with e-stant software and USB serial cable
- Remote programming: telephone (DTMF tones), SMS (created with e-stant software)
- Alarm sending modes: voice, CLI, Esse-ti protocol, P100, SMS
- Voice prompts: menu with 5 languages, customizable with SW e-stant or micro SD card
- Multifunction relay
- Alarm ending with or without reset codes
- Local and remote teso of any kind of alarm
- Technological alarms: low battery, battery replacement, power supply failure, diagnostic, auxiliary, SIM card expiring
- Multi-Sharing function: simultaneous notification of the same alarm to different receivers
- SD Card: extended LOG, firmware update, custom voice prompts and parameter settings



Handsfree Speaker Units

- 6CV-30022 MICROPHONE** - Soldered on shielded cable L= 3 m.
- 5KT-020 PRE-WIRED KIT** - Inclusive of shielded cable with microphone for the lift car, pre-cabled yellow and green LEDs, stainless-steel Led-holder plate (80x40 mm), free wires for connection with the existing emergency-call pushbutton, speaker unit with button for the car bottom.
- 5HV-036 PASSIVE SPEAKER UNIT** - With microphone and loudspeaker.
- 5HV-021 PASSIVE SPEAKER UNIT WITH CABLE** L = 3 m - With microphone, loudspeaker, emergency pushbutton and shielded cable L = 3 m.
- 5HV-103 STAINLESS-STEEL PANEL WITH PASSIVE SPEAKER UNIT** - with microphone, loudspeaker, pushbutton and LEDs with pictograms.

Machine Room Terminals

- 4TS-101 ST 100L ANALOG TELEPHONE WITH DISPLAY**
- 5TE-016 FLY-LIFT ANALOG TELEPHONE**
- 5TE-018 SLIM ANALOG TELEPHONE** with keypad on the receiver.

Accessories

- 5HV-170/1 INDUCTION LOOP** - Communication aid device for hearing-impaired. Comes with inductive wire and amplifier unit.

