




Dimensions: 157x96x28 mm
Weight: 233 g


HELPHY COMPACT-V


Ultra-compact alarm system


- Autodialer with speaker unit
- Flexible installation behind the COP or on top-of-car
- Full range 10-30Vdc power supply
- Programmable with e-stant freeware software

Handsfree Speaker Units

- 


6CV-30022 MICROPHONE - Soldered on shielded cable L = 3 m.
- 


5HV-036 PASSIVE SPEAKER UNIT - With microphone and loudspeaker.
- 


5HV-021 PASSIVE SPEAKER UNIT WITH CABLE L = 3 m - With microphone, loudspeaker, emergency pushbutton and shielded cable L = 3 m.
- 

5HV-103 STAINLESS-STEEL PANEL WITH PASSIVE SPEAKER UNIT - with microphone, loudspeaker, pushbutton and LEDs with pictograms.

Machine Room Terminals


- 


4TS-101 ST 100L ANALOG TELEPHONE WITH DISPLAY
- 


5TE-016 FLY-LIFT ANALOG TELEPHONE
- 

5TE-018 SLIM ANALOG TELEPHONE with keypad on the receiver.

Accessories


- 


5HV-170/1 INDUCTION LOOP - Communication aid device for hearing-impaired. Comes with inductive wire and amplifier unit.
- 

5HA-005 ST-POWER 12V - 12V universal power supply.
- 

7BA-10003 BACKUP BATTERY 12V 1,3A/H - to be installed inside the ST-POWER 12V.

GATEWAY 4G/3G/2G

- 

5IG-260/S 4G.VoLTE - 4G/LTE/UMTS/GSM MODULE complete with: backup batteries, adapter, magnet-base antenna. Voice over VoLTE service with fallback on 2G/3G network.
- 

5IG-161/S GSM500 - GD - 2G Quad-band module complete with: back up batteries, adapter, magnet-base antenna and extension cable L = 2 m.

HELPHY COMPACT-V

5HL-620

HELPHY COMPACT-V: autodialer in metal case complete with:
- speaker unit
- LEDs signalling alarm sent/received/operation status.
Ready for connection over the PSTN line, expandible over the GSM line.

Main Features

- Telephone numbers: programmable, up to 12
 - Supported voice terminals: 2 passive speaker units
 - Digital volume adjustment
 - Voice and data GSM expansion
 - Local programming: telephone (DTMF tones), micro SD card, computer with e-stant software and USB serial cable
 - Remote programming: telephone (DTMF tones), software compliant with EPT protocol (DTMF)
 - VoIP compatibility: with analog output or with ATA adapter
 - Alarm sending modes: voice, CLI, Esse-ti protocol, P100, SMS (only with 4G.VoLTE)
 - Voice prompts: menu with 9 languages, customizable with SW e-stant or micro SD card
- Multifunction relay
 - Alarm ending with or without reset codes
 - Extra inputs for lift remote-monitoring applications
 - Technological alarms: low battery, battery replacement, power supply failure, built-in speaker unit diagnostic, auxiliary, alarm ending, stuck pushbutton, LMS functionality, power supply restore, timer
 - Multi-link function: up to 9 autodialers can be connected over 1 telephone line
 - SD Card: extended LOG, firmware update, custom voice prompts and parameters setting.

